

ENGINE STARTING APPARATUS

CROSS-REFERENCES TO RELATED APPLICATIONS

[0001] This nonprovisional application claims priority under 35 U.S.C. § 119(a) on Patent Application Nos. 2001-030706 and 2001-333345 filed in Japan on February 7, 2001 and October 30, 2001, respectively, the entirety of which is herein incorporated by reference.

BACKGROUND OF THE INVENTION

1. Field of the invention:

[0002] The present invention relates to an engine starting apparatus. In particular, the present invention relates to an engine starting apparatus in which a starting power transmission is provided between a starter motor and a crankshaft. The starter motor rotates by electric power supplied from a battery. The starting power transmission decelerates the rotation power of the starter motor and transmits the power to the crankshaft.

2. Description of Related Art:

[0003] Conventionally, such apparatus is already well known by e.g. Japanese Patent No. 3070086. In this apparatus, in a mono-cylinder engine, the starter motor and starting power transmission means are downsized without setting excessively high strength by providing a torque limiter mechanism in a starting power transmission. The torque limiter protects the starter motor against reverse operation of the crankshaft upon engine startup.

[0004] Furthermore, as disclosed in e.g. Japanese Published Unexamined Patent Application No. Hei 4-148008, the starter motor and starting power transmission are downsized without setting an excessively high strength. The starter motor is prevented against reverse operation of the crankshaft by opening an exhaust valve through a decompression device in an initial compression stroke upon startup of mono-cylinder engine.

[0005] In a mono-cylinder engine, as in the case of the above-described conventional art, the starter motor and starting power transmission can be downsized by providing a torque limiter mechanism or decompression device. However, it is difficult to apply the above conventional art construction to a multi-cylinder engine without any change. Specifically, in a multi-cylinder engine, ignition is made at an early timing in spite of a great amount of inertia of the crankshaft. Accordingly, the crankshaft cannot be started without difficulty unless a limiter weight is set to a large value. Furthermore, the decompression device cannot be actuated within a range of a small crank angle without difficulty, and the downsizing and weight reduction of the starter motor and starting power transmission in the multi-cylinder engine cannot be attained without difficulty.

SUMMARY OF THE INVENTION

[0006] The present invention has been made in view of the above situation, and has as its object to provide an engine starting apparatus which attains downsizing and weight reduction of a starter motor and starting power transmission even in a multi-cylinder engine.

[0007] To attain the foregoing object, the present invention is directed to an engine starting apparatus, wherein a starting power transmission is provided between a starter motor and a crankshaft. The starter motor rotates by electric power supplied from a

battery. The starting power transmission decelerates the rotation power of the starter motor and transmits the power to the crankshaft. The engine starting apparatus includes a decompression device for depressing an exhaust valve to open the exhaust valve, in correspondence with actuation of an actuator; a revolution detector that detects the number of revolutions of the crankshaft; and a controller for controlling the actuation of the actuator by starting the actuation of said actuator in accordance with the actuation of the starter motor and continuing the actuation of said actuator until the number of revolutions detected by the revolution detector reaches a predetermined number of revolutions.

[0008] According to this construction, the power from the starter motor is transmitted via the starting power transmission to the crankshaft in correspondence with the actuation of the starter motor. Since the actuator of the decompression device starts in accordance with the actuation of the starter motor and the exhaust valve is depressed to open the exhaust valve, the pressure in a combustion chamber during an engine compression stroke is reduced, and the engine starting torque can be greatly reduced. Furthermore, the open status of the exhaust valve depressed by the decompression device ends when the number of revolutions of the crankshaft has reached the predetermined number of revolutions. Since the crankshaft has a sufficient inertia even when the combustion chamber pressure in the engine compression stroke increases to a normal state, the engine can be reliably started. In this manner, since the starting torque necessary upon engine startup can be reduced, and the decompression device is continuously actuated until the number of revolutions of the crankshaft reaches the predetermined number of revolutions regardless of ignition timing, the downsizing and weight reduction of the starter motor and starting power transmission can be attained even in a multi-cylinder engine.

[0009] Furthermore, the present invention includes, in addition to the construction of the present invention described above, the starting power transmission provided with a one-way clutch having a clutch member as one constituent that rotates at a speed higher than that of the crankshaft and that is always coupled to the crankshaft. According to this construction, the comparatively large inertia produced by the clutch member as one constituent of the one-way clutch is effectively utilized as inertia of the crankshaft. Accordingly, startup of the engine can be improved.

[0010] Further scope of applicability of the present invention will become apparent from the detailed description given hereinafter. However, it should be understood that the detailed description and specific examples, while indicating preferred embodiments of the invention, are given by way of illustration only, since various changes and modifications within the spirit and scope of the invention will become apparent to those skilled in the art from this detailed description.

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] The present invention will become more fully understood from the detailed description given hereinbelow and the accompanying drawings which are given by way of illustration only, and thus are not limitative of the present invention, and wherein:

[0012] Figure 1 is a cross-sectional view of a part of the structure of the engine;

[0013] Figure 2 is a side view of the engine mounted on an aircraft;

[0014] Figure 3 is a cross-sectional view along the line 3-3 in Figure 2; and

[0015] Figure 4 is an enlarged cross-sectional view along the line 4-4 in Figure 2.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0016] Hereinbelow, a working example of the present invention will be described in accordance with an embodiment of the present invention illustrated in the attached drawing.

[0017] Figures 1 to 4 show a working example of the present invention. Figure 1 is a cross-sectional view of a part of the structure of an engine. Figure 2 is a side view of the engine mounted on an aircraft. Figure 3 is a cross-sectional view along a line 3-3 in Figure 2. Figure 4 is an enlarged cross-sectional view along a line 4-4 in Figure 2.

[0018] First, in Figure 1, the engine E is a horizontally opposed multi-cylinder engine having e.g. 2 cylinders. The engine E can be mounted on a vehicle, for example, an automobile, a motorcycle, an aircraft and the like. In the engine E, large ends of connecting rods 4 are respectively coupled to plural crank pins 2a of a crankshaft 2 rotatably supported in a crankcase 1. Small ends of the respective connecting rods 4 are coupled to pistons (not shown) respectively slidably engaged in plural cylinder bores 3 partially overlapped with each other in a plane projection including an axial line of the crankshaft 2.

[0019] One end of the crankshaft 2 projects from the crankcase 1. A rotor 6 of a generator 5 is coaxially coupled to the one end of the crankshaft 2. A stator 7 of the generator 5 is fixedly supported by a support plate 8 fixed to the crankcase 1. Furthermore, a cover 9 for covering the generator 5 is fastened to the crankcase 1.

[0020] A first gear 10 is fixed to the crankshaft 2 between the crankcase 1 and the support plate 8. A rotary shaft 12 is rotatably supported by the crankcase 1 and the support plate 8. A second gear 11 is fixed to the rotary shaft 12 and is engaged with the first gear 10. Furthermore, a third gear 13 is integrally formed with the rotary shaft 12. The third gear 13 is engaged with a fourth gear 14 connected to a valve device 45.

[0021] A water pump 15 is attached to the cover 9. A pump shaft 16 of the water pump 15 is connected, coaxially and relatively-unrotatable, to the rotary shaft 12. Rotation power from the crankshaft 2 is transmitted to the water pump 15 via the first gear 10, the second gear 11 and the rotary shaft 12.

[0022] A gear case 17 is constructed by connecting a pair of case members 18 and 19 together. The gear case 17 is connected to the cover 9. A starter motor 21, which rotates by electric power supplied from a battery 20, is provided outside the crankcase 1. The starter motor has a rotation axial line parallel to the crankshaft 2 and is supported by the gear case 17. A starting power transmission 22 is provided between the starter motor 21 and the crankshaft 2.

[0023] The starting power transmission 22 includes a deceleration gear array 23 accommodated in the gear case 17 so as to decelerate and transmit the output from the starter motor 21. A one-way clutch 24 is accommodated in the gear case 17. A damper spring 25 is provided between the deceleration gear array 23 and the one-way clutch 24. A flywheel 26 is fastened to a clutch outer member 33 as a clutch member constructing a part of the one-way clutch 24. A rotary shaft 27 is coaxially connected to the flywheel 26. Furthermore, a fifth gear 28 is integrally formed with the rotary shaft 27 such that the fifth gear engages with the first gear 10 of the crankshaft 2.

[0024] A cylindrical shaft 31a of a gear 31 is rotatably supported by a support shaft 30, which has both ends supported in the gear case 17. The cylindrical shaft 31a is press-inserted in a gear 29, which constructs a part of the deceleration gear array 23. The shaft 31a can be slid into to the gear 29 upon input of excessive torque by surface processing on the shaft 31a. Specifically, the shaft 31a and the gear 29 construct a torque limiter mechanism.

[0025] The one-way clutch 24 has a clutch inner member 32 coupled to the deceleration gear array 23 via the damper spring 25 and the clutch outer member 33. The one-way

clutch 24 transmits rotation power in one direction, inputted into the clutch inner member 32 from the deceleration gear array 23 side, to the clutch outer member 33 side. When a revolution speed in the one direction of the clutch outer member 33 connected to the crankshaft 2 exceeds the revolution speed of the clutch inner member 32 during startup of the engine E, the clutch blocks power transmission between the clutch inner member 32 and the clutch outer member 33.

[0026] The rotary shaft 27 is rotatably supported by the crankcase 1 and the cover 9. The rotary shaft 27 has one end projecting into the gear case 17. The flywheel 26 is spline-coupled to the one end of the rotary shaft 27 in the gear case 17. Furthermore, a bolt 34, which is engaged with an outer surface of the flywheel 26, is engaged with the rotary shaft 27.

[0027] The fifth gear 28 has a diameter smaller than that of the first gear 10. The fifth gear 28 is integrally formed with the other end of the rotary shaft 27 and is engaged with the first gear 10 of the crankshaft 2. The flywheel 26 and the clutch outer member 33, which rotate with the rotary shaft 27, are always coupled to the crankshaft 2. The flywheel 26 and the clutch outer member 33 rotate at a speed higher than that of the crankshaft 2.

[0028] A relay 36 is provided between the starter motor 21 and the battery 20. Power supply and supply stoppage from the battery 20 to the starter motor 21, i.e., actuation and stoppage of actuation of the starter motor 21 is controlled by connection/disconnection of the relay 36 in correspondence with connection/disconnection of a starter switch 35.

[0029] Exhaust valves 38 are openenably/closably provided in respective cylinders of a cylinder head 37 of the engine E. The exhaust valve 38 is opened/closed by the valve device 45. The valve device 45 includes a holder 40. A lifter housing 39 is coaxial with an opening/closing actuation axial line of the exhaust valve 38, and is fixed to the

cylinder head 37. A rocker arm 42 is swingably supported by a rocker shaft 41 fixedly supported by the holder 40. A push rod 43 applies an upward pressing force to one end of the rocker arm 42. A lifter 44 is located between the other end of the rocker arm 42 and the exhaust valve 38. The lifter 44 is slidably engaged in the lifter housing 39.

[0030] A decompression cam 46 is engaged with an engaging arm 42a provided on the other end side of the rocker arm 42 in the valve device 45. The decompression cam 46 and a solenoid 47 construct a decompression device 48. The solenoid 47 acts as an actuator coupled to the rotatable decompression cam 46.

[0031] The decompression device 48 depresses and opens the exhaust valve 38 by rotation of the decompression cam 46 through actuation of the solenoid 47. The actuation of the solenoid 47 is controlled by the controller 49.

[0032] The starter switch 35 is connected to the controller 49 for detection of the actuation period of the starter motor 21. Furthermore, a detection value from the revolution detector 52 is inputted into the controller 49. The revolution detector 52 is attached to the cover 9 in a position opposite to the outer peripheral surface of the rotor 6 in the generator 5, and detects the number of revolutions of the crankshaft 2.

[0033] The controller 49 starts the actuation of the solenoid 47 in accordance with the actuation of the starter motor 21 to depress the exhaust valve 38 to open the exhaust valve 38. The controller 49 continues the actuation of the solenoid 47 until the number of revolutions detected by the revolution detector 52 reaches a predetermined number of revolutions, which is a sufficiently high value. Accordingly, controller 49 controls the actuation of the solenoid 47.

[0034] Furthermore, the controller 49 controls actuation of an ignition device 50 to ignite ignition plugs 51, 51 of the engine E. It is desirable that the controller 49 control the ignition device 50 to start ignition of the ignition plugs 51 in correspondence

with stoppage of actuation of the solenoid 47, i.e. stoppage of actuation of the decompression device 48. It is desirable that, similar to the ignition start timing of the ignition plugs 51, fuel injection start timing by a fuel injection valve (not shown) is determined after the stoppage of actuation of the decompression device 48.

[0035] In a case where this engine E is mounted on an aircraft 150 as shown in Figure 2, the engine E is accommodated in a cowl 152 attached to a front part of body 151 such that the axial line of the crankshaft 2 is set along in frontward/rearward directions. The engine E is elastically supported by a support frame 153 provided in the cowl 152.

[0036] A spinner 155 having plural propellers 154 is provided in front of the cowl 152. The crankshaft 2 of the engine E is coaxially coupled to the spinner 155.

[0037] Referring to Figure 3, an intake manifold 156 extending in the frontward/rearward directions is provided above the engine E. Both front sides of the intake manifold 156 are connected to left and right cylinder heads 37, 37 of the engine E via intake pipes 55, 55.

[0038] Furthermore, an air cleaner 157 is connected to a rear part of the intake manifold 156. The air cleaner is provided on the rear side from the engine E and in a position rear and below the intake manifold 156. A suction pipe 158 is connected to a lower part of the air cleaner 157. The suction pipe 158 extends below the engine E to the front side thereof. A front end of the suction pipe 158 is open to a screen 159 provided in a front lower end part of the cowl 152.

[0039] Radiators 160, 160 are provided on both left and right sides of a lower part of the engine E. The radiators 160, 160 are accommodated in a pair of first air ducts 161, 161 extending frontward and upward. Lower ends of the first air ducts 161, 161 are open toward a diagonally rear direction in the cowl 152. A second air duct 162 is connected to upper ends of the first air ducts 161, 161. The second air duct 162 has a common duct 162a with an air intake port 163 facing the screen 159 in a front-end

central portion, extending leftward/rightward below a front part of the engine E. A pair of branch ducts 162b, 162b are connected to the upper ends of the first air ducts 161, 161. The branch ducts 162b, 162b extend rearward and upward from left and right ends of the common duct 162a.

[0040] Specifically, the radiators 160, 160 are provided on the left and right sides of the lower part of the engine E and are cooled by air from the screen 159 at the front end of the cowl 152. The air is pressed from the propellers 154 to the air intake port 163, and passed from the second air duct 162 to the left and right first air ducts 161, 161.

[0041] The support frame 153 is formed by combining, e.g. plural pipe members so as to hold the engine E from a rear position. On the other hand, attachment arms 164, 164 are provided such that the arms are positioned at respective corners of virtual right rectangle with, e.g. the axial line of the crankshaft 21 as a center in a plane orthogonal to the axial line, in e.g. four positions in a rear part of a crankcase 19 of the engine E. The attachment arms 164, 16 are inclined such that a distance therebetween increases as the arms are positioned toward the rear side. The attachment arms 164, 164 are attached to the support frame 153 via elastic mounts 165, 165.

[0042] Referring to Figure 4, the elastic mount 165 include a cylindrical collar 166, a cylindrical support pipe 167 coaxially surrounding the collar 166, fixed to the support frame 153, and mount rubber 168. The mount rubber 168 is inserted between the collar 166 and the support pipe 167, with inner and outer peripheries hardened to an outer periphery of the collar 166 and an inner periphery of the support pipe 167. The ends of the collar 166 project from the ends of the support pipe 167.

[0043] A pressing plate 169 is brought into contact with one end of the collar 166. The other end of the collar is in contact with the attachment arm 164. Thus, a bolt 170 with an enlarged-diameter head 170a is engaged with the attachment arm 164 of the engine E. The bolt 170 engages an outer surface of the pressing plate 169, and is

inserted through the pressing plate 169 and the collar 166. The attachment arm 164, i.e. the engine E is elastically attached to the support frame 153 by tightening the bolt 170.

[0044] The operation of the embodiment according to the present invention will now be described. When the actuation of the starter motor 21 is started by bringing the starter switch 35 into conduction so as to start the engine E, the power from the starter motor 21 is transmitted via the starting power transmission 22 to the crankshaft 2. In correspondence with the actuation of the starter motor 21, the controller 49 actuates the solenoid 47 of the decompression device 48, and the exhaust valve 38 is depressed and thereby opened by the decompression cam 46. Accordingly, the pressure in the combustion chamber during a compression stroke of the engine E is reduced, and the starting torque of the engine E can be greatly reduced. Furthermore, the open state of the exhaust valve 38 depressed by the decompression device 48 ends when the number of revolutions of the crankshaft 2 has reached a predetermined number of revolutions and the crankshaft 2 has sufficient inertia even when the pressure in the combustion chamber during the compression stroke of the engine E increases to a normal state. Accordingly, the engine E can be reliably started, and the starting torque necessary upon startup of the engine E can be reduced.

[0045] The decompression device 48 continues actuation until the number of revolutions of the crankshaft 2 reaches the predetermined number of revolutions regardless of ignition timing. Accordingly, downsizing and weight reduction of the starter motor 21 and the starting power transmission 22 can be attained even in a multicylinder engine E such as a 2-cylinder engine.

[0046] Furthermore, the starting power transmission 22 is provided with a one-way clutch 24 having the clutch outer member 33, which rotates at a speed higher than that of the crankshaft 2 and which is always coupled to the crankshaft 2, as one constituent.

The comparatively large inertia produced by the clutch outer member 33 can be effectively utilized as the inertia of the crankshaft 2, thereby the startup of the engine E can be improved. Especially, as in the case of this embodiment where the flywheel 26 is fastened to the clutch outer member 33, the greater inertia produced by the clutch outer member 33 and the flywheel 26 is effectively utilized as inertia of the crankshaft 2, thereby the startup of the engine E can be further improved.

[0047] Furthermore, if it is arranged such that the ignition of the ignition plugs 51 is started and fuel injection is started, in correspondence with the stoppage of actuation of the decompression device 48, the startup of the engine E can be further improved.

[0048] As described above, the embodiment of the present invention has been described, however, the present invention is not limited to the above embodiment, but various design changes may be made without departing from the present invention described in the scope of the claims.

[0049] For example, a multi-cylinder engine E has been described in the above embodiment; however, the present invention is also applicable to a mono-cylinder engine.

[0050] As described above, according to the present invention, the starting torque of the engine is greatly reduced by reducing the pressure in the combustion chamber during the compression stroke of the engine until the number of revolutions of the crankshaft reaches a predetermined number of revolutions. Thus, the engine can be reliably started, and the downsizing and weight reduction of the starter motor and starting power transmission can be attained even in a multicylinder engine.

[0051] Furthermore, the comparatively large inertia produced by the clutch member as one constituent of the one-way clutch is effectively utilized as inertia of the crankshaft. Accordingly, the startup of the engine E can be improved.

[0052] The invention being thus described, it will be obvious that the same may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the invention, and all such modifications as would be obvious to one skilled in the art are intended to be included within the scope of the following claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218